



Mirror Gold ACT | 30.801ACTN

This polyester printable mirror film is suitable for indoor and short-term outdoor use. With a gold mirror finish, it seamlessly adapts to flat and 2D curved surfaces, providing design flexibility. The film features Air Channel Technology (ACT) to prevent air bubbles and wrinkles during application and has a clear protection film.

FACE FILM

PET, gloss gold mirror

Thickness (µm)	180
Opacity	High

ADHESIVE

Clear solvent-based acrylic, permanent

Thickness (µm)	25
Adhesion to steel	FINAT FTM 1
20 minutes (180°) N/25mm	8
24 hours (180°) N/25mm	8

RELEASE LINER

Clear structured PET liner

Thickness (µm)	75
----------------	----

PROTECTION FILM

Thickness (µm)	20
----------------	----

PRODUCT APPLICATION

Application method	Wet & dry
Application temperature (°C)	10 to 30
Service temperature (°C)	-45 to 130



DURABILITY

Shelf life (months)	18	
Outdoor durability (years)	1	Vertical exposure, Mid-EU climate

REGULATIONS & CERTIFICATIONS

Fire rating	EN 13501-1 (Class B)
-------------	----------------------

ROLL SIZES

1220mm x 50m
1220mm x 25m

PRINTING METHOD

UV* & Latex *Angular alignment of printheads only
Tested on Mimaki UCJV 300-160

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.

