



Dusted Etch PET | 31.130N

Dusted Etch PET is a PVC-free film and a more sustainable choice. With its UV-cured adhesive, it helps reduce VOC emissions. It has an anti-scratch top layer, making it the best choice for high-traffic areas.

FACE FILM

PET, matt grey

Thickness (µm)	75
----------------	----

ADHESIVE

Clear UV-cured, removable

Thickness (µm)	50
Adhesion to steel	FINAT FTM 1
20 minutes (180°) N/25mm	5
24 hours (180°) N/25mm	6

RELEASE LINER

Synthetic liner

Thickness (µm)	50
----------------	----

PRODUCT APPLICATION

Application method	Wet
Application temperature (°C)	10 to 30
Service temperature (°C)	-20 to 70

DURABILITY

Shelf life (months)	24	
Outdoor durability (years)	N/A	Vertical exposure, Mid-EU climate

CERTIFICATES

Fire rating	EN 13501-1 (Class B-s1, d0)
-------------	-----------------------------

ROLL SIZES

1520mm x 30m

PRINTING METHOD

UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.

