



33.011N | RayGuard UV Shield

RayGuard UV Shield blocks UV rays from the sun, preventing indoor furniture and objects from fading or aging.

SOLAR CHARACTERISTICS

Mirror Effect (%)	9
Blocked UV Transmission (%)	99,5
Natural Light Transmission (%)	90
Total Solar Energy Rejection (TSER) (%)	14
Solar Energy Absorption (%)	7
Solar Glare Reduction (%)	13
G-Value	0,85

Data calculated based on film applied to clear glass (3mm thick)

FACE FILM

Multi-layered PET, invisible

Thickness (µm)	50
----------------	----

RELEASE LINER

Clear PET

Thickness (µm)	12
----------------	----

PRODUCT APPLICATION

Application temperature (°C)	+5
Service temperature (°C)	-30 to 80
Storage temperature (°C)	-5 to 40
Application type	Interior

DURABILITY

Outdoor durability (years)	10	Vertical exposure, Mid-EU climate
Shelf life (months)	36	

CERTIFICATES

Fire Rating	M1
REACH RoHS	Compliant



ROLL SIZES

1520mm x 30,5m

INSTALLATION

Recommended installation

On clear, tinted or reflective tinted single pane and clear, tinted, reflective tinted, gasfilled or laminated double pane.

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.