



StrongTack | 40.100N

A monomeric PVC film equipped with a high tack adhesive system, guaranteeing exceptional adhesion on challenging surfaces, such as PE and PP, known for their low energy properties making them difficult to adhere to.

FACE FILM

Monomeric PVC, gloss white

Thickness (µm)	100	
Opacity	High	
Tensile strength (N/mm ²)	>58	EN ISO 527-3
Elongation at break (%)	>170	EN ISO 527-3

ADHESIVE

Clear solvent-based acrylic, high tack permanent

Thickness (µm)	25	
Adhesion to steel		FINAT FTM 1
20 minutes (180°) N/25mm	21	
24 hours (180°) N/25mm	28	

RELEASE LINER

Lay-flat kraft paper liner, double-sided PE-coated

Weight (gsm)	140	
--------------	-----	--

PRODUCT APPLICATION

Application method	Dry	
Dimensional stability (.mm)	<1,2	FINAT FTM 14
Application temperature (°C)	10 to 30	
Service temperature (°C)	-10 to 60	



DURABILITY

Shelf life (months)	12	
Outdoor durability (years)	4	Vertical exposure, Mid-EU climate

ROLL SIZES

1220mm x 50m
1370mm x 50m

PRINTING METHOD

(Eco)-Solvent, Latex, UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.

