



Total Erazе Clear | 50.000N

Total Erazе Clear is a high-gloss transparent film for creating custom whiteboards by laminating it onto printed vinyls, walls, or cardboard. Its low-energy lacquer coating ensures effortless ink removal. For best performance, pair it with our 51.102N StrongTouch Supreme print film and use the 97.011 Erazе Marker Black or check the Total Erazе marker compatibility list.

FACE FILM

Polymeric PVC, gloss clear

Thickness (µm)	100	
Tensile strength (N/mm ²)	>15	EN ISO 527-3
Elongation at break (%)	>80	EN ISO 527-3

ADHESIVE

Clear water-based acrylic, permanent

Thickness (µm)	20	
Adhesion to steel		FINAT FTM 1
20 minutes (180°) N/25mm	10	
24 hours (180°) N/25mm	18	

RELEASE LINER

Lay-flat kraft paper liner, one-sided PE-coated

Weight (gsm)	
--------------	--

PRODUCT APPLICATION

Application method	Wet & dry
Application temperature (°C)	10 to 30
Service temperature (°C)	-40 to 95



DURABILITY

Shelf life (months)	12
Outdoor durability (years)	Vertical exposure, Mid-EU climate

ROLL SIZES

1350mm x 50m

PRINTING METHOD

UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.

