



Crystal Clear | 50.001N

Crystal Clear is a transparent print film designed for window graphics. Made from polymeric PVC with an ultra-clear adhesive, it becomes nearly invisible once applied. Its high-gloss surface enhances the print with added depth and vibrancy.

FACE FILM

Polymeric PVC, gloss ultra clear

Thickness (µm)	75	
Tensile strength (N/mm ²)	45	EN ISO 527-3
Elongation at break (%)	30	EN ISO 527-3

ADHESIVE

Clear solvent-based acrylic, semi-permanent

Thickness (µm)	25	
Adhesion to steel		FINAT FTM 1
20 minutes (180°) N/25mm	9	
24 hours (180°) N/25mm	12	

RELEASE LINER

Contrast PET liner, anti-static

Thickness (µm)	75
----------------	----

PRODUCT APPLICATION

Application method	Wet & dry
Dimensional stability	<0,5
Application temperature (°C)	10 to 30
Service temperature (°C)	-20 to 70



DURABILITY

Shelf life (months)	12	
Outdoor durability (years)	7	Vertical exposure, Mid-EU climate

ROLL SIZES

1370mm x 50m
1520mm x 50m

PRINTING METHOD

(Eco)-Solvent, Latex, UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.

