



ForceTack ACT | 51.100ACTN

ForceTack ACT provides outstanding dimensional stability and durability. Its soft, polymeric vinyl is perfect for both interior and exterior use. The high-tack adhesive delivers excellent performance on challenging surfaces, while Air Channel Technology (ACT) prevents air bubbles and wrinkles during application.

FACE FILM

Polymeric PVC, satin white

Thickness (µm)	100	
Opacity	High	
Tensile strength (N/mm ²)	>22	EN ISO 527-3
Elongation at break (%)	>150	EN ISO 527-3

ADHESIVE

Clear solvent-based acrylic, high tack permanent

Thickness (µm)	40	
Adhesion to steel		FINAT FTM 1
20 minutes (180°) N/25mm	30	
24 hours (180°) N/25mm	35	

RELEASE LINER

Structured lay-flat kraft paper liner

Weight (gsm)	140
--------------	-----

PRODUCT APPLICATION

Application method	Dry
Dimensional stability (.mm)	<0,5
Application temperature (°C)	10 to 30
Service temperature (°C)	-20 to 70



DURABILITY

Shelf life (months)	12	
Outdoor durability (years)	8	Vertical exposure, Mid-EU climate

ROLL SIZES

1370mm x 50m

PRINTING METHOD

(Eco)-Solvent, Latex, UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.

