



StrongTouch | 51.101N

StrongTouch features a top-tier acrylic adhesive, enabling film removal within 12 months while ensuring prolonged sticking capability. Ideal for temporary floor signs, decals, or point-of-purchase ads on walls and counters.

FACE FILM

Polymeric PVC, matt white

Thickness (µm)	90	
Opacity	Medium	
Elongation at break (%)	>120	EN ISO 527-3

ADHESIVE

Clear solvent-based acrylic, high tack removable

Thickness (µm)	25	
Adhesion to steel		FINAT FTM 1
20 minutes (180°) N/25mm	14	
24 hours (180°) N/25mm	16	

RELEASE LINER

Lay-flat kraft paper liner, double-sided PE-coated

Weight (gsm)	140	
--------------	-----	--

PRODUCT APPLICATION

Application method	Dry	
Dimensional stability (.mm)	<0,3	FINAT FTM 14
Application temperature (°C)	10 to 30	
Service temperature (°C)	-20 to 70	



DURABILITY

Shelf life (months)	12	
Outdoor durability (years)	8	Vertical exposure, Mid-EU climate

REGULATIONS & CERTIFICATIONS

Fire protection	EN 13501-1 (Class B)
-----------------	----------------------

ROLL SIZES

1370mm x 50m

PRINTING METHOD

(Eco)-Solvent, Latex, UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.

