



StrongTouch Supreme | 51.102N

StrongTouch Supreme effortlessly adjusts to uneven surfaces, thanks to its specially formulated plasticizers. It's coated with an exceptionally high-performance adhesive, enabling the film to be removed for up to 12 months while retaining its long-lasting sticking capability.

FACE FILM

Polymeric PVC, satin white

Thickness (µm)	90	
Opacity	High	
Elongation at break (%)	>145	EN ISO 527-3

ADHESIVE

Clear solvent-based acrylic, high tack removable

Thickness (µm)	50	
Adhesion to steel		FINAT FTM 1
20 minutes (180°) N/25mm	9	
24 hours (180°) N/25mm	10	

RELEASE LINER

Lay-flat kraft paper liner, double-sided PE-coated

Weight (gsm)	140	
--------------	-----	--

PRODUCT APPLICATION

Application method	Dry	
Dimensional stability	<0,3	
Application temperature (°C)	10 to 30	
Service temperature (°C)	-20 to 70	

DURABILITY

Shelf life (months)	12	
Outdoor durability (years)	8	Vertical exposure, Mid-EU climate



REGULATIONS & CERTIFICATIONS

Fire Rating EN 13501-1 (Class B)

ROLL SIZES

1370mm x 50m

1520mm x 50m

PRINTING METHOD

(Eco)-Solvent, Latex, UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.

