51.110N | SlipStop White

A polymeric PVC with an R10 anti-slip certification, a universally removable adhesive, and print compatibility with eco-solvent, latex, and UV inks. It offers moderate slip resistance, ideal for applications such as retail floor promotions and wayfinding (shops and supermarkets), as well as indoor entrance zones and busy hallways where occasional wetness may occur.

FACE FILM

Polymeric PVC, textured white

Thickness (µm)	150
Opacity	High

ADHESIVE

Clear microsphere acrylic, removable

Thickness (µm)	20	
Adhesion to steel		FINAT FTM 1
20 minutes (180°) N/25mm	4	
24 hours (180°) N/25mm	5	

RELEASE LINER

Lay-flat kraft paper, one-sided PE coated

Weight (gsm)	135

PRODUCT APPLICATION

Application method	Dry
Application temperature (°C)	10 to 30
Service temperature (°C)	-20 to 70

DURABILITY

Shelf life (months)	12
Outdoor durability (year)	5

CERTIFICATES

Anti-Slip rating	R10	DIN 51130
Fire rating	EN 4102-1 (Class B)	
HP Latex	Certified	

ROLL SIZES

1370mm x 30,5 m

PRINTING METHOD

(Eco)-Solvent, (HP) Latex, UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.