



StrongTouch Plus | 51.111N

StrongTouch Plus features a UV-cured adhesive combined with a highly opaque white face film. It is ideal for temporary floor graphics, decals, and point-of-purchase displays on smooth or slightly textured walls and counters.

FACE FILM

Polymeric PVC, matt white

| | |
|----------------|------|
| Thickness (µm) | 90 |
| Opacity | high |

ADHESIVE

Clear UV-cured, high tack removable

| | |
|--------------------------|-------------|
| Thickness (µm) | 50 |
| Adhesion to steel | FINAT FTM 1 |
| 20 minutes (180°) N/25mm | 13 |
| 24 hours (180°) N/25mm | 14 |

RELEASE LINER

Lay-flat kraft paper liner

| | |
|--------------|-----|
| Weight (gsm) | 140 |
|--------------|-----|

PRODUCT APPLICATION

| | |
|------------------------------|-----------|
| Application method | Dry |
| Application temperature (°C) | 10 to 30 |
| Service temperature (°C) | -20 to 70 |

DURABILITY

| | |
|----------------------------|-------------------------------------|
| Shelf life (months) | 12 |
| Outdoor durability (years) | 5 Vertical exposure, Mid-EU climate |

ROLL SIZES

1370mm x 50m

PRINTING METHOD

(Eco)-Solvent, Latex, UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.

