



Silver Etch ACT | 51.121ACTN

This high-quality translucent polymeric film features a silver etched glass effect, providing privacy and style to office windows. Perfect for decorative applications, it enhances professionalism and aesthetics while Air Channel Technology (ACT) prevents air bubbles and wrinkles during application.

FACE FILM

Polymeric PVC, satin grey glitter

Thickness (µm)	70	
Tensile strength (N/mm ²)	>45	EN ISO 527-3
Elongation at break (%)	>50	EN ISO 527-3

ADHESIVE

Clear water-based acrylic, permanent

Thickness (µm)	25	
Adhesion to steel		FINAT FTM 1
20 minutes (180°) N/25mm	16	
24 hours (180°) N/25mm	21	

RELEASE LINER

Structured lay-flat kraft paper liner, one-sided PE coated

Weight (gsm)	140
--------------	-----

PRODUCT APPLICATION

Application method	Dry
Dimensional stability (.mm)	<0,5
Application temperature (°C)	10 to 30
Service temperature (°C)	-20 to 70

DURABILITY

Shelf life (months)	12	
Outdoor durability (years)	7	Vertical exposure, Mid-EU climate



CERTIFICATES

Fire rating EN 13501-1 (Class B)

ROLL SIZES

1220mm x 50m
1520mm x 50m

PRINTING METHOD

(eco)solvent, UV & latex

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.

