



## Crystal Etch | 51.125N

Crystal Etch is a premium vinyl that mimics the look of etched glass, designed for both indoor and outdoor use. With excellent plotting and weeding properties, this film is ideal for creating detailed window decals.

### FACE FILM

Polymeric PVC, satin grey glitter

Thickness (µm)	70	
Tensile strength (N/mm <sup>2</sup> )	>45	EN ISO 527-3
Elongation at break (%)	>180	EN ISO 527-3

### ADHESIVE

Clear solvent-based acrylic, permanent

Thickness (µm)	25	
Adhesion to steel		FINAT FTM 1
20 minutes (180°) N/25mm	15	
24 hours (180°) N/25mm	20	

### RELEASE LINER

Lay-flat kraft paper liner, one-sided PE coated

Weight (gsm)	140
--------------	-----

### PRODUCT APPLICATION

Application method	Wet & dry
Dimensional stability (.mm)	<0,5
Application temperature (°C)	10 to 30
Service temperature (°C)	-20 to 70

### DURABILITY

Shelf life (months)	12	
Outdoor durability (years)	7	Vertical exposure, Mid-EU climate



**CERTIFICATES**

Fire rating

EN 13501-1 (Class B)

---

**ROLL SIZES**

1220mm x 50m

**PRINTING METHOD**

(eco)solvent, UV & latex

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.

