



Ultra Chrome Black | 73.902N

Ultra Chrome is a metallised film designed to replicate the look of polished metals with a striking mirror-like finish. Conformable and highly extensible, it is easy to apply on flat or slightly curved surfaces and, with skilled installation, can be used on complex curves if not overstretched to protect the metallised surface. The low-tack adhesive allows for easy repositioning during application. For plotter-cut detailing and all exterior applications, edge-sealing is required to prevent corrosion of the metallic layer and maintain warranty coverage.

FACE FILM

PVC, glossy mirror black

Thickness (µm)	50	
Opacity	High	
Tensile strength (N/mm ²)	56	EN ISO 527-3
Elongation at break (%)	180	EN ISO 527-3

ADHESIVE

White solvent-based acrylic, permanent

Thickness (µm)	30	
Adhesion to steel		FINAT FTM 1
20 minutes (180°) N/25mm	16	
24 hours (180°) N/25mm	20	

RELEASE LINER

Clear PET liner

Thickness (µm)	150	
----------------	-----	--

PROTECTION FILM

Thickness (µm)	20	
----------------	----	--



PRODUCT APPLICATION

Application method	Dry	
Dimensional stability (.mm)	<0,5	FINAT FTM 14
Application temperature (°C)	10 to 30	
Service temperature (°C)	-15 to 60	

DURABILITY

Shelf life (months)	12	
Outdoor durability (years)	4	Vertical exposure, Mid-EU climate

ROLL SIZES

920mm x 10m

920mm x 20m

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.

